

WI 120TU

Device information	WI 120TU
Design	
- Heat source	Water
- Model	Universal design
- Thermal energy metering	Integrated
- Installation location	Indoors
- Performance levels	2
Operating limits	
- Max. flow temperature ⁷⁾	62 °C +/- 2
- Lower operating limit heat source (heating operation) / Upper operating limit heat source (heating operation)	7 / 25 °C
- Free compression circulating pump heating (max. level)	41000 Pa
Flow / sound	
- Max. heating water flow rate / Pressure drop	20,1 m³/h / 21500 Pa
- Minimum heating water flow rate / Pressure drop	11,6 m³/h / 6700 Pa
- Heat source flow (min.) / Pressure drop evaporator EN 14511	22,0 m³/h / 22000 Pa
- Sound power level	66 dB (A)
- Sound pressure level in 1 m (indoors) ²⁾	53 dB (A)
Dimensions/weight and filling quantities	
- Weight	608 kg
- Thread type, heating connection / Connection heating	Rp / 2 ½ inch
- Thread type, heat source connection / Heat source connection	Rp / 2 ½ inch
- Refrigerant / Amount of refrigerant	R410A / 23,0 kg
- Oil type / Oil quantity	Polyolester (POE) / 7,8 l
- Water content	21 l
- Volume of the heat transfer medium in the device	21 l
- Buffer tank	Nein
Electrical connection	
- Rated voltage / Fuse protection	3/PE ~400 V, 50 Hz / C 80 A
- Control voltage / Control voltage fuse protection	1/N/PE ~230 V, 50 Hz / C 13 A
- Degree of protection	IP 21
- Initial current limiter	Yes
- Starting current	76 A
- Nominal power consumption according to EN 14511 at W10/W35 / Maximum electric power consumption ¹⁾	19,2 / 35,3 kW
- Nominal current at W10/W35 / cos phi	34,6 A / 0,8
- Power consumption of the compressor protection / Control compressor protection	90 W / thermostatically controlled
- Power input of integrated pump	0,48 kW
Additional model features	
- Water in device protected against freezing ⁴⁾	Yes



Glen Dimplex Thermal Solutions
 (Glen Dimplex Deutschland GmbH)
 Am Goldenen Feld 18
 D-95326 Kulmbach
 T: + 49 9221 709-100
 F: + 49 9221 709-339
 dimplex@dimplex.de
 www.dimplex.de

Glen Dimplex Austria GmbH
 Hauptstraße 71
 A-5302 Henndorf am Wallersee
 T: + 43 6214 20330
 F: + 43 6214 203304
 info@dimplex.at
 www.dimplex.at

WI 120TU

Heat output / coefficient of performance (COP) according to EN 14511:1)

Heizen 1 Verdichter	W35	W45	W55
W10	64.3 kW / 6.9	57.5 kW / 4.9	49.6 kW / 3.5
W25			
Heizen 2 Verdichter	W35	W45	W55
W10	117.4 kW / 6.1	111.6 kW / 4.7	106.3 kW / 3.8
W25			

Note:

1) This data indicates the size and capacity of the system according to EN 14511. For an analysis of the economic and energy efficiency of the system, the bivalence point and regulation should be taken into consideration. These specifications can only be achieved with clean heat exchangers. Information on maintenance, commissioning and operation can be found in the respective sections of the installation and operating instructions. The specified values have the following meaning, e.g. A7 / W35: Heat source temperature 7 °C and heating water flow temperature 35 °C.

2) The specified sound pressure level corresponds to the operating noise of the heat pump in heating operation with a flow temperature of 35°C. The specified sound pressure level represents the free sound area level. The measured value can deviate by up to 16 dB(A), depending on the installation location.

4) The heat circulating pump and the heat pump manager must always be ready for operation.

7) Depending on the heat pump type and refrigerant used, the maximum flow temperatures in heating operation may be reduced when the outside temperature falls. Further information can be found in the operating limit diagram for the heat pump. If the supporting feet are used, the level can increase by up to 3 dB (A).




Glen Dimplex Thermal Solutions
(Glen Dimplex Deutschland GmbH)
Am Goldenen Feld 18
D-95326 Kulmbach
T: + 49 9221 709-100
F: + 49 9221 709-339
dimplex@dimplex.de
www.dimplex.de

Glen Dimplex Austria GmbH
Hauptstraße 71
A-5302 Henndorf am Wallersee
T: + 43 6214 20330
F: + 43 6214 203304
info@dimplex.at
www.dimplex.at

WI 120TU

Heating water temperature [°C]



Heat source inlet temperature [°C]

Note:

The maximum possible flow temperature and the operating limits vary by $\pm 2\text{K}$ due to component tolerances.

The minimum volume flow specified in the device information must be ensured at the lower operating limit.

In mono energy operating mode with the heating element activated, the maximum flow temperature increases by approximately 3K.



Glen Dimplex Thermal Solutions
(Glen Dimplex Deutschland GmbH)
Am Goldenen Feld 18
D-95326 Kulmbach
T: + 49 9221 709-100
F: + 49 9221 709-339
dimplex@dimplex.de
www.dimplex.de

Glen Dimplex Austria GmbH
Hauptstraße 71
A-5302 Henndorf am Wallersee

T: + 43 6214 20330
F: + 43 6214 203304
info@dimplex.at
www.dimplex.at