

## Data sheet SI 50TUR



### Reversible brine-to-water heat pump for indoor installation.

Max. flow temperature: 62 °C

Heat pump for heating and cooling with two performance levels for increased efficiency in partial load operation for indoor installation and integrated heat pump manager WPM Econ5 with standard display. Variable connection options for brine and heating connections on the back board of the casing. A sound-optimised metal casing and the integrated solid-borne sound insulation with free-swinging compressor base plate make direct connection with the heating system possible. Access for service work from the front, no minimum clearance required on the sides, accessible from underneath with a lift truck. High coefficient of performance through electronic expansion valve, COP booster and electronic pump control depending on the temperature spread in the brine and generator circuit. Optimised heating and cooling operation via an internal hydraulic four-way reversing valve which is activated by the controller. Sensor monitoring of the refrigeration circuit for a high degree of operational safety and integrated thermal energy metering (display of the calculated quantity of thermal energy for heating, domestic hot water and swimming pool water preparation). FWO function for more efficient domestic hot water preparation with increased domestic hot water temperatures and volumes of water to be drawn through optimised tank charging.

Universal design with two compressors for output regulation when operating at partial load, optional domestic hot water preparation and flexible expansion options for:

- Bivalent or bivalent-renewable operating mode
- Distribution systems with unmixed and mixed heating circuits
- Use of load-variable tariffs (SG Ready)

Soft starter, flow



Glen Dimplex Thermal Solutions T: + 49 9221 709-100  
(Glen Dimplex Deutschland GmbH) F: + 49 9221 709-339  
Am Goldenen Feld 18 dimplex@dimplex.de  
D-95326 Kulmbach www.dimplex.de

Glen Dimplex Austria GmbH  
Hauptstraße 71  
A-5302 Henndorf am Wallersee

T: + 43 6214 20330  
F: + 43 6214 203304  
info@dimplex.at  
www.dimplex.at

## SI 50TUR

and return sensors for the brine and heating circuit integrated. Dirt trap for brine circuit, external sensor (standard NTC-2), circulating pumps for brine and heat generator circuit in the scope of supply (observe the free compression). Brine circulating pump 12 m delivery height at 6 m<sup>3</sup>/h, flange connection DN 40, installation length 250 mm; heat generator circuit pump 8 m delivery height at 6 m<sup>3</sup>/h, flange connection DN 40, installation length 220 mm. Heat pump white textured (similar to RAL 9003). Brine package SZB must be ordered separately.



Glen Dimplex Thermal Solutions T: + 49 9221 709-100  
(Glen Dimplex Deutschland GmbH) F: + 49 9221 709-339  
Am Goldenen Feld 18 dimplex@dimplex.de  
D-95326 Kulmbach www.dimplex.de

Glen Dimplex Austria GmbH T: + 43 6214 20330  
Hauptstraße 71 F: + 43 6214 203304  
A-5302 Henndorf am Wallersee info@dimplex.at  
www.dimplex.at

# SI 50TUR

## Technical data

### Dimplex Reversible brine-to-water heat pump for indoor installation. (Medium temperature)

|                                                                                                               |                        |
|---------------------------------------------------------------------------------------------------------------|------------------------|
| Heat pump code                                                                                                | 6009                   |
| Max. flow temperature                                                                                         | 62 Grad                |
| Lower operating limit heat source (heating operation) / Upper operating limit heat source (heating operation) | -5 Grad / 25 Grad      |
| Sound power level                                                                                             | 61 dB(A)               |
| Refrigerant / Amount of refrigerant                                                                           | R410A / 8,7 kg         |
| Max. heating water flow rate / Pressure drop                                                                  | 8,4 m3 pro h / 5000 Pa |
| Heat source flow (min.)                                                                                       | 9,3 m3 pro h           |
| Width x Height x Depth **                                                                                     | 1000 x 1665 x 805 mm   |
| Weight                                                                                                        | 490 kg                 |
| Rated voltage                                                                                                 | 3/PE ~400 V, 50 Hz     |
| Starting current                                                                                              | 49 A                   |
| Fuse protection HP with separate infeed ***                                                                   | C 40 A                 |
| Heat pump seal of approval (valid until)                                                                      | Yes / 23.11.2022       |

\*\*Please note that additional space is required for pipe connections, operation and maintenance.

\*\*\*



Glen Dimplex Thermal Solutions T: + 49 9221 709-100  
(Glen Dimplex Deutschland GmbH) F: + 49 9221 709-339  
Am Goldenen Feld 18 dimplex@dimplex.de  
D-95326 Kulmbach www.dimplex.de

Glen Dimplex Austria GmbH  
Hauptstraße 71  
A-5302 Henndorf am Wallersee

T: + 43 6214 20330  
F: + 43 6214 203304  
info@dimplex.at  
www.dimplex.at

# SI 50TUR

| Description                                      | Order ref. | Article number | Sample item | Item |
|--------------------------------------------------|------------|----------------|-------------|------|
| <b>Heat pumps</b>                                |            |                |             |      |
| Elasticated sound insulation underlay strips     | SYL 250    | 352260         | 0           |      |
| Connecting flange for heating and brine circuits | AF 65      | 351920         | 0           |      |
| <b>Hydraulic accessories</b>                     |            |                |             |      |
| Universal buffer tank (500 l)                    | PSW 500    | 339210         | 1           |      |
| Transport aid for Hydro-Tower / LAW indoor unit  | TH 270     | 370430         | 0           |      |
| RWT 500 finned tube heat exchanger               | RWT 500    | 339840         |             |      |
| Immersion heater 4.5 kW; ~230 V                  | CTHK 630   | 363610         | 0           |      |
| Immersion heater 2.0 kW; ~230 V                  | CTHK 631   | 336180         | 0           |      |
| Immersion heater 2.9 kW; ~400 V                  | CTHK 632   | 335910         | 0           |      |
| Immersion heater 4.5 kW; ~400 V                  | CTHK 633   | 322140         | 0           |      |
| Immersion heater 6.0 kW; ~400 V                  | CTHK 634   | 322150         | 0           |      |
| Immersion heater 7.5 kW                          | CTHK 635   | 322160         | 0           |      |



Glen Dimplex Thermal Solutions T: + 49 9221 709-100  
 (Glen Dimplex Deutschland GmbH) F: + 49 9221 709-339  
 Am Goldenen Feld 18 dimplex@dimplex.de  
 D-95326 Kulmbach www.dimplex.de

Glen Dimplex Austria GmbH T: + 43 6214 20330  
 Hauptstraße 71 F: + 43 6214 203304  
 A-5302 Henndorf am Wallersee info@dimplex.at  
 www.dimplex.at

# Data sheet SI 50TUR

| Description                                                    | Order ref.    | Article number | Sample item | Item |
|----------------------------------------------------------------|---------------|----------------|-------------|------|
| Freestanding buffer tank 1000 l heating/cooling                | BTHC 1000     | 381980         | 0           |      |
| Freestanding buffer tank 1000 l heating/cooling                | PSP 1000K     | 376240         | 0           |      |
| Manifold bar for DN 50 modules                                 | VTB 50        | 367730         | 0           |      |
| Domestic hot water module/unmixed heating circuit module       | WWM 50        | 364250         | 0           |      |
| Electronically controlled wet-running pump, self-regulating    | UPE 120-32K   | 374740         | 0           |      |
| High-efficiency wet-running pump PWM with coupling relay       | UPH 120-32PK  | 375750         | 0           |      |
| Electronically controlled circulating pump with coupling relay | UPH 80-40F    | 371800         | 0           |      |
| Electronically controlled circulating pump with coupling relay | UPH 120-50F   | 379020         | 0           |      |
| DN 50 double-sphere rubber expansion joint                     | KOMP 50       | 362080         | 0           |      |
| <b>Heating accessories</b>                                     |               |                |             |      |
| Heat pump heater heating/passive cooling, depth 16.5 cm        | WPHK 165080   | 381210         | 0           |      |
| Heat pump heater heating/passive cooling, depth 16.5 cm        | WPHK 1650100  | 381220         | 0           |      |
| Heat pump heater heating/passive cooling, depth 16.5 cm        | WPHK 1650140  | 381230         | 0           |      |
| Heat pump heater heating/passive cooling, depth 16.5 cm        | WPHK 1650180  | 381240         | 0           |      |
| Heat pump heater heating/passive cooling, depth 21.5 cm        | WPHK 2150100  | 381250         | 0           |      |
| Heat pump heater heating/passive cooling, depth 21.5 cm        | WPHK 2150140  | 381260         | 0           |      |
| Heat pump heater heating/passive cooling, depth 21.5 cm        | WPHK 2150180  | 381270         | 0           |      |
| Heat pump heater vertical                                      | WPHKV 1220053 | 381280         | 0           |      |
| <b>DHW preparation accessories</b>                             |               |                |             |      |
| Domestic hot water cylinder (500l) with temperature sensor     | WWSP 556      | 370080         | 1           |      |
| FLH 25M flange heater                                          | FLH 25M       | 349430         | 0           |      |



Glen Dimplex Thermal Solutions  
(Glen Dimplex Deutschland GmbH)  
Am Goldenen Feld 18  
D-95326 Kulmbach  
T: + 49 9221 709-100  
F: + 49 9221 709-339  
dimplex@dimplex.de  
www.dimplex.de

Glen Dimplex Austria GmbH  
Hauptstraße 71  
A-5302 Henndorf am Wallersee  
T: + 43 6214 20330  
F: + 43 6214 203304  
info@dimplex.at  
www.dimplex.at

# Data sheet SI 50TUR

| Description                                                              | Order ref.  | Article number | Sample item | Item |
|--------------------------------------------------------------------------|-------------|----------------|-------------|------|
| Flange heater for domestic hot water                                     | FLH 60      | 338060         | 0           |      |
| Flange heater for domestic hot water                                     | FLHU 70     | 338070         | 0           |      |
| Safety valve combination                                                 | SVK 852     | 326660         | 0           |      |
| Domestic hot water cylinder, 700 litres                                  | WWSP 770    | 376730         | 0           |      |
| 3-way reversing valve DN 50                                              | DWV 50      | 374800         | 1           |      |
| Actuator for 3-way reversing valves DWV 25 - 50                          | EMA DWV     | 374760         | 1           |      |
| Pump unit DN 32 for direct connection of the domestic hot water cylinder | WPG 32      | 356040         | 0           |      |
| <b>Control accessories</b>                                               |             |                |             |      |
| Extension for an Ethernet network connection                             | NWPM Touch  | 378800         | 1           |      |
| Expansion module WPM for a KNX/EIB connection                            | KNX WPM     | 376350         | 0           |      |
| Extension for a Modbus RTU connection                                    | LWPM 410    | 339410         | 0           |      |
| Outside temperature sensor with casing                                   | FG 3115     | 336620         | 0           |      |
| Temperature sensor NTC-10 with metal sleeve                              | NTC-10M     | 363600         | 0           |      |
| <b>Accessories for passive cooling</b>                                   |             |                |             |      |
| Passive cooling controller                                               | WPM Econ PK | 360000         | 0           |      |



Glen Dimplex Thermal Solutions  
(Glen Dimplex Deutschland GmbH)  
Am Goldenen Feld 18  
D-95326 Kulmbach

T: + 49 9221 709-100  
F: + 49 9221 709-339  
dimplex@dimplex.de  
www.dimplex.de

Glen Dimplex Austria GmbH  
Hauptstraße 71  
A-5302 Henndorf am Wallersee

T: + 43 6214 20330  
F: + 43 6214 203304  
info@dimplex.at  
www.dimplex.at

# Data sheet SI 50TUR

| Description                                                   | Order ref.   | Article number | Sample item | Item |
|---------------------------------------------------------------|--------------|----------------|-------------|------|
| Plate heat exchanger for SIH 40                               | WTE 40       | 358430         | 0           |      |
| Plate heat exchanger, copper-soldered                         | WTU 50       | 362370         | 0           |      |
| Plate heat exchanger for SI 50                                | WTE 50       | 358440         | 0           |      |
| <b>Control accessories (cooling)</b>                          |              |                |             |      |
| Dew point monitor                                             | TPW WPM      | 350970         | 0           |      |
| Room climate station for temperature and humidity measurement | RKS WPM      | 342220         | 0           |      |
| <b>Solar thermal systems accessories</b>                      |              |                |             |      |
| 400l solar cylinder for heat pump                             | WWSP 432 SOL | 361080         | 0           |      |
| 500 l solar cylinder for heat pump                            | WWSP 540 SOL | 361090         | 0           |      |

\* Other specific accessories available / required

Important information:

The combination of the components and the quantities indicated represent a non-binding sample system, which needs to be tested and individually adapted as required. Pump dimensioning must be reviewed according to the pressure loss of the system and the minimum heating water flow rate of the heat pump.



Glen Dimplex Thermal Solutions  
(Glen Dimplex Deutschland GmbH)  
Am Goldenen Feld 18  
D-95326 Kulmbach  
T: + 49 9221 709-100  
F: + 49 9221 709-339  
dimplex@dimplex.de  
www.dimplex.de

Glen Dimplex Austria GmbH  
Hauptstraße 71  
A-5302 Henndorf am Wallersee

T: + 43 6214 20330  
F: + 43 6214 203304  
info@dimplex.at  
www.dimplex.at