

# Data sheet SI 35TUR

## Reversible brine-to-water heat pump for indoor installation.

Installation location:

Max. flow temperature: 62 °C

Casing colour: RAL 9003

Heat pump for heating and cooling with two performance levels for increased efficiency in partial load operation for indoor installation and integrated heat pump manager WPM Econ5 with touch display. Variable connection options for brine and heating connections on the back board of the casing. A sound-optimised metal casing and the integrated solid-borne sound insulation with free-swinging compressor base plate make direct connection with the heating system possible. High coefficients of performance (COP) through electronic expansion valve and electronic pump control depending on the temperature spread in the brine and generator circuit. Optimised heating and cooling operation via an internal hydraulic four-way reversing valve which is activated by the controller. Sensor monitoring of the refrigeration circuit for a high degree of operational safety and integrated thermal energy metering (display of the calculated quantity of thermal energy for heating, domestic hot water and swimming pool water preparation). FWO function for more efficient domestic hot water preparation with increased domestic hot water temperatures and volumes of water to be drawn through optimised tank charging. Universal design with two compressors for output regulation when operating at partial load, optional domestic hot water preparation and flexible expansion options for:

- Bivalent or bivalent-renewable operating mode
- Distribution systems with unmixed and mixed heating circuits
- Use of load-variable tariffs (SG Ready)

Soft starter, flow and return sensors for the brine and heating circuit integrated. Dirt trap for brine circuit, external sensor (standard NTC-2), circulating



Glen Dimplex Thermal Solutions T: + 49 9221 709-100  
(Glen Dimplex Deutschland GmbH) F: + 49 9221 709-339  
Am Goldenen Feld 18 dimplex@dimplex.de  
D-95326 Kulmbach www.dimplex.de

Glen Dimplex Austria GmbH T: + 43 6214 20330  
Hauptstraße 71 F: + 43 6214 203304  
A-5302 Henndorf am Wallersee info@dimplex.at  
www.dimplex.at

# SI 35TUR

pumps for brine and heat generator circuit in the scope of supply (observe the free compression). Brine circulating pump 12 m delivery height at 6 m<sup>3</sup>/h, flange connection DN 40, installation length 250 mm; heat generator circuit pump 12 m delivery height at 5 m<sup>3</sup>/h (thread connection R 1 1/4", (pump thread 2"), inside micrometer 180 mm! Heat pump white textured (similar to RAL 9003). Brine package SZB must be ordered separately.



Glen Dimplex Thermal Solutions T: + 49 9221 709-100  
(Glen Dimplex Deutschland GmbH) F: + 49 9221 709-339  
Am Goldenen Feld 18 dimplex@dimplex.de  
D-95326 Kulmbach www.dimplex.de

Glen Dimplex Austria GmbH T: + 43 6214 20330  
Hauptstraße 71 F: + 43 6214 203304  
A-5302 Henndorf am Wallersee info@dimplex.at  
www.dimplex.at

# SI 35TUR

## Technical data

### Dimplex Reversible brine-to-water heat pump for indoor installation. (Medium temperature)

Heat pump code	6008
Max. flow temperature	62 Grad
Lower operating limit heat source (heating operation) / Upper operating limit heat source (heating operation)	-5 Grad / 25 Grad
Sound power level	58 dB(A)
Refrigerant / Amount of refrigerant	R410A / 8,0 kg
Max. heating water flow rate / Pressure drop	5,9 m3 pro h / 11000 Pa
Heat source flow (min.)	6,7 m3 pro h
Width x Height x Depth **	1000 x 885 x 810 mm
Weight	305 kg
Rated voltage	3/PE ~400 V, 50 Hz
Starting current	35 A
Fuse protection HP with separate infeed ***	C 25 A
Heat pump seal of approval (valid until)	No

\*\*Please note that additional space is required for pipe connections, operation and maintenance.

\*\*\*



Glen Dimplex Thermal Solutions T: + 49 9221 709-100  
(Glen Dimplex Deutschland GmbH) F: + 49 9221 709-339  
Am Goldenen Feld 18 dimplex@dimplex.de  
D-95326 Kulmbach www.dimplex.de

Glen Dimplex Austria GmbH T: + 43 6214 20330  
Hauptstraße 71 F: + 43 6214 203304  
A-5302 Henndorf am Wallersee info@dimplex.at  
www.dimplex.at

# SI 35TUR

Description	Order ref.	Article number	Sample item	Item
<b>Heat pumps</b>				
Elasticated sound insulation underlay strips	SYL 250	352260	0	
DN 40 dirt trap	SMF 40	362150	0	
DN 40 double-sphere rubber expansion joint	KOMP 40	362070	0	
<b>Hydraulic accessories</b>				
Built-under buffer tank 300l	PSP 300U	378630	1	
Immersion heater 4.5 kW; ~230 V	CTHK 630	363610	0	
Immersion heater 2.0 kW; ~230 V	CTHK 631	336180	0	
Immersion heater 2.9 kW; ~400 V	CTHK 632	335910	0	
Immersion heater 4.5 kW; ~400 V	CTHK 633	322140	0	
Immersion heater 6.0 kW; ~400 V	CTHK 634	322150	0	
Immersion heater 7.5 kW	CTHK 635	322160	0	
Immersion heater 9.0 kW; ~400 V	CTHK 636	322170	0	
Universal buffer tank (500 l)	PSW 500	339210	0	
Freestanding buffer tank 1000 l heating/cooling	PSP 1000K	376240	0	
Dual differential pressureless manifold	DDV 40	367720	1	
Manifold bar DN 32	VTB 32-2	374920	0	
Manifold bar DN 32	VTB 32-3	374930	0	
Domestic hot water module/unmixed heating circuit module	WWM 32	367800	0	
Mixed heating circuit module	MMH 32	367790	1	
Mixer module for bivalent systems	MMB 32	367780	0	



Glen Dimplex Thermal Solutions T: + 49 9221 709-100  
 (Glen Dimplex Deutschland GmbH) F: + 49 9221 709-339  
 Am Goldenen Feld 18 dimplex@dimplex.de  
 D-95326 Kulmbach www.dimplex.de

Glen Dimplex Austria GmbH T: + 43 6214 20330  
 Hauptstraße 71 F: + 43 6214 203304  
 A-5302 Henndorf am Wallersee info@dimplex.at  
 www.dimplex.at

# Data sheet SI 35TUR

Description	Order ref.	Article number	Sample item	Item
Electronically controlled wet-running pump, self-regulating	UPE 100-32K	374730	1	
Electronically controlled wet-running pump, self-regulating	UPE 120-32K	374740	0	
Ready-for-use DN 32 stainless steel Wellflex pipe	VSE 32-50	362520	0	
Ready-for-use DN 32 stainless steel Wellflex pipe	VSE 32-100	362530	0	
Ready-for-use DN 32 stainless steel Wellflex pipe	VSE 32-150	362540	0	
Ready-for-use DN 32 stainless steel Wellflex pipe	VSE 32-200	362550	0	
Ready-for-use DN 32 stainless steel Wellflex pipe	VSE 32-300	362560	0	
<b>Heating accessories</b>				
Fan convector heating with EC fan	SRX 080EM	367500	0	
Fan convector heating with EC fan	SRX 120EM	367510	0	
Fan convector heating with EC fan	SRX 140EM	367520	0	
Fan convector heating with EC fan	SRX 180EM	367530	0	
<b>DHW preparation accessories</b>				
Domestic hot water cylinder (500l) with temperature sensor	WWSP 556	370080	1	
FLH 25M flange heater	FLH 25M	349430	0	
Flange heater for domestic hot water	FLH 60	338060	0	
Flange heater for domestic hot water	FLHU 70	338070	0	
Safety valve combination	SVK 852	326660	0	



Glen Dimplex Thermal Solutions T: + 49 9221 709-100  
 (Glen Dimplex Deutschland GmbH) F: + 49 9221 709-339  
 Am Goldenen Feld 18 dimplex@dimplex.de  
 D-95326 Kulmbach www.dimplex.de

Glen Dimplex Austria GmbH T: + 43 6214 20330  
 Hauptstraße 71 F: + 43 6214 203304  
 A-5302 Henndorf am Wallersee info@dimplex.at  
 www.dimplex.at

# Data sheet SI 35TUR

Description	Order ref.	Article number	Sample item	Item
Domestic hot water cylinder, 700 litres	WWSP 770	376730	0	
Pump unit DN 32 for direct connection of the domestic hot water cylinder	WPG 32	356040	0	
High-efficiency wet-running pump PWM with coupling relay	UPH 120-32PK	375750	0	
3-way reversing valve DN 40	DWV 40	374790	1	
Actuator for 3-way reversing valves DWV 25 - 50	EMA DWV	374760	1	
Actuator for 3-way reversing valves DWV 25 - 50	EMA DWV	374760	1	
<b>Control accessories</b>				
Extension for an Ethernet network connection	NWPM	356960	1	
Expansion module WPM for a KNX/EIB connection	KNX WPM	376350	0	
Extension for a Modbus RTU connection	LWPM 410	339410	0	
Outside temperature sensor with casing	FG 3115	336620	0	
Temperature sensor NTC-10 with metal sleeve	NTC-10M	363600	0	
Remote control for WPM 2006/2007/EconPlus/R	AP PGD	356570	0	
<b>Accessories for passive cooling</b>				
Passive cooling station with cooling controller	PKS 25 Econ	362940	0	
Plate heat exchanger, copper-soldered	WTU 50	362370	0	
<b>Control accessories (cooling)</b>				
Passive cooling controller	WPM Econ PK	360000	0	
Dew point monitor	TPW WPM	350970	0	
Dew point sensor	TPF 341	350980	0	
<b>Solar thermal systems accessories</b>				
400l solar cylinder for heat pump	WWSP 432 SOL	361080	0	
500 l solar cylinder for heat pump	WWSP 540 SOL	361090	0	

\* Other specific accessories available / required

Important information:

The combination of the components and the quantities indicated represent a non-binding sample system, which needs to be tested and



Glen Dimplex Thermal Solutions  
 (Glen Dimplex Deutschland GmbH)  
 Am Goldenen Feld 18  
 D-95326 Kulmbach  
 T: + 49 9221 709-100  
 F: + 49 9221 709-339  
 dimplex@dimplex.de  
 www.dimplex.de

Glen Dimplex Austria GmbH  
 Hauptstraße 71  
 A-5302 Henndorf am Wallersee  
 T: + 43 6214 20330  
 F: + 43 6214 203304  
 info@dimplex.at  
 www.dimplex.at

individually adapted as required. Pump dimensioning must be reviewed according to the pressure loss of the system and the minimum heating water flow rate of the heat pump.

## SI 35TUR



Glen Dimplex Thermal Solutions T: + 49 9221 709-100  
(Glen Dimplex Deutschland GmbH) F: + 49 9221 709-339  
Am Goldenen Feld 18 dimplex@dimplex.de  
D-95326 Kulmbach www.dimplex.de

Glen Dimplex Austria GmbH T: + 43 6214 20330  
Hauptstraße 71 F: + 43 6214 203304  
A-5302 Henndorf am Wallersee info@dimplex.at  
www.dimplex.at