



## Data sheet WI 65TU

### High efficiency water-to-water heat pump for indoor installation.

Installation location:

Max. flow temperature: 62 °C

Casing colour: White (similar to RAL 9003)

Heat pump for heating purposes with two performance levels for increased efficiency in partial load operation for indoor installation and integrated heat pump manager WPM Econ5Plus with standard display. Variable connection options for the water and heating connections on the rear wall of the casing. A sound-optimised metal casing and the integrated solid-borne sound insulation with free-swinging compressor base plate make direct connection with the heating system possible. Access for service work front and left, no minimum clearance is required on the right side. High coefficient of performance through electronic expansion valve, COP booster and electronic pump control depending on the temperature spread in the heat generator circuit. Sensor monitoring of the refrigeration circuit for a high degree of operational safety and integrated thermal energy metering (display of the calculated quantity of thermal energy for heating, domestic hot water and swimming pool water preparation). FWO function for more efficient domestic hot water preparation with increased domestic hot water temperatures and volumes of water to be drawn through optimised tank charging.

Universal design with two compressors for output regulation when operating at partial load, optional domestic hot water preparation and flexible expansion options for:

- Bivalent or bivalent-renewable operating mode
- Distribution systems with unmixed and mixed heating circuits
- Use of load-variable tariffs (SG Ready)

Soft starter, flow and return sensors for the water and heating circuit integrated. External sensor (standard NTC-2) and circulating pump for the heat generator circuit in the scope of supply (note free compression). Heat pump white textured (similar to RAL 9003). Heat generator circuit pump 8 m delivery height at 6 m<sup>3</sup>/h, flange connection DN 40, installation length 220 mm.



Glen Dimplex Thermal Solutions  
(Glen Dimplex Deutschland GmbH) T: + 49 9221 709-100  
Am Goldenen Feld 18 F: + 49 9221 709-339  
D-95326 Kulmbach dimplex@dimplex.de  
www.dimplex.de

Glen Dimplex Austria GmbH  
Hauptstraße 71  
A-5302 Henndorf am Wallersee

T: + 43 6214 20330  
F: + 43 6214 203304  
info@dimplex.at  
www.dimplex.at

# WI 65TU

## Technical data

### Dimplex High efficiency water-to-water heat pump for indoor installation. (Medium temperature)

Heat pump code	3010
Max. flow temperature	62 Grad
Lower operating limit heat source (heating operation) / Upper operating limit heat source (heating operation)	7 Grad / 25 Grad
Sound power level	61 dB(A)
Refrigerant / Amount of refrigerant	R410A / 16,8 kg
Max. heating water flow rate / Pressure drop	12,1 m <sup>3</sup> pro h / 10200 Pa
Heat source flow (min.)	12,5 m <sup>3</sup> pro h
Width x Height x Depth **	1000 x 1665 x 805 mm
Weight	465 kg
Rated voltage	3/PE ~400 V, 50 Hz
Starting current	56 A
Fuse protection HP with separate infeed ***	C 40 A
Heat pump seal of approval (valid until)	Yes / 23.11.2022

\*Delivery time on request.

\*\*Please note that additional space is required for pipe connections, operation and maintenance.

\*\*\*



Glen Dimplex Thermal Solutions  
(Glen Dimplex Deutschland GmbH) T: + 49 9221 709-100  
Am Goldenen Feld 18 F: + 49 9221 709-339  
D-95326 Kulmbach dimplex@dimplex.de  
www.dimplex.de

Glen Dimplex Austria GmbH  
Hauptstraße 71  
A-5302 Henndorf am Wallersee  
info@dimplex.at  
www.dimplex.at

T: + 43 6214 20330  
F: + 43 6214 203304  
info@dimplex.at  
www.dimplex.at

# WI 65TU

Description	Order ref.	Article number	Sample item	Item
<b>Heat pumps</b>				
Elasticated sound insulation underlay strips	SYL 250	352260	0	
DN 40 dirt trap	SMF 40	362150	0	
DN 40 double-sphere rubber expansion joint	KOMP 40	362070	0	
<b>Hydraulic accessories</b>				
Free-standing heating buffer tank 1000 litre	BTH 1000	382090	0	
Universal buffer tank (500 l)	PSW 500	339210	1	
Transport aid for Hydro-Tower / LAW indoor unit	TH 270	370430	0	
RWT 500 finned tube heat exchanger	RWT 500	339840		
Immersion heater 4.5 kW; ~230 V	CTHK 630	363610	0	
Immersion heater 2.0 kW; ~230 V	CTHK 631	336180	0	
Immersion heater 2.9 kW; ~400 V	CTHK 632	335910	0	
Immersion heater 4.5 kW; ~400 V	CTHK 633	322140	0	
Immersion heater 6.0 kW; ~400 V	CTHK 634	322150	0	
Immersion heater 7.5 kW	CTHK 635	322160	0	



Glen Dimplex Thermal Solutions  
 (Glen Dimplex Deutschland GmbH) T: + 49 9221 709-100  
 Am Goldenen Feld 18 F: + 49 9221 709-339  
 D-95326 Kulmbach dimplex@dimplex.de  
 www.dimplex.de

Glen Dimplex Austria GmbH  
 Hauptstraße 71 T: + 43 6214 20330  
 A-5302 Henndorf am Wallersee F: + 43 6214 203304  
 info@dimplex.at  
 www.dimplex.at

# Data sheet WI 65TU

Description	Order ref.	Article number	Sample item	Item
Free-standing buffer tank 1000 l	PSW 1000	361640	0	
Manifold bar for DN 50 modules	VTB 50	367730	0	
Domestic hot water module/unmixed heating circuit module	WWM 50	364250	1	
Victaulic coupling on R 2"	VCC 50	367750	0	
Electronically controlled wet-running pump, self-regulating	UPE 120-32K	374740	0	
High-efficiency wet-running pump PWM with coupling relay	UPH 120-32PK	375750	1	
Electronically controlled circulating pump with coupling relay	UPH 80-40F	371800	0	
Electronically controlled circulating pump with coupling relay	UPH 120-50F	379020	0	
DN 50 double-sphere rubber expansion joint	KOMP 50	362080	0	
<b>Heating accessories</b>				
Heat pump heater heating/passive cooling, depth 16.5 cm	WPHK 165080	381210	72	
Heat pump heater heating/passive cooling, depth 16.5 cm	WPHK 1650100	381220	72	
Heat pump heater heating/passive cooling, depth 16.5 cm	WPHK 1650140	381230	72	
Heat pump heater heating/passive cooling, depth 16.5 cm	WPHK 1650180	381240	72	
Heat pump heater heating/passive cooling, depth 21.5 cm	WPHK 2150100	381250	72	
Heat pump heater heating/passive cooling, depth 21.5 cm	WPHK 2150140	381260	72	
Heat pump heater heating/passive cooling, depth 21.5 cm	WPHK 2150180	381270	72	
Heat pump heater vertical	WPHKV 1220053	381280	72	
<b>DHW preparation accessories</b>				



Glen Dimplex Thermal Solutions  
 (Glen Dimplex Deutschland GmbH) T: +49 9221 709-100  
 Am Goldenen Feld 18 F: +49 9221 709-339  
 D-95326 Kulmbach dimplex@dimplex.de  
 www.dimplex.de

Glen Dimplex Austria GmbH  
 Hauptstraße 71  
 A-5302 Henndorf am Wallersee

T: +43 6214 20330  
 F: +43 6214 203304  
 info@dimplex.at  
 www.dimplex.at

# Data sheet WI 65TU

Description	Order ref.	Article number	Sample item	Item
Domestic hot water cylinder (500l) with temperature sensor	WWSP 556	370080	0	
Domestic hot water cylinder, 700 litres	WWSP 770	376730	1	
FLH 25M flange heater	FLH 25M	349430	0	
Flange heater for domestic hot water	FLHU 70	338070	0	
Flange heater for domestic hot water	FLH 60	338060	0	
Flange heater for domestic hot water	FLH 90	366130	0	
Safety valve combination	SVK 852	326660	0	
3-way reversing valve DN 50	DWV 50	374800	1	
Actuator for 3-way reversing valves DWV 25 - 50	EMA DWV	374760	1	
<b>Control accessories</b>				
Flow rate switch DN 65	DFS 60-95	369990	1	
Extension for an Ethernet network connection	NWPM Touch	378800	1	
Expansion module WPM for a KNX/EIB connection	KNX WPM	376350	0	
Extension for a Modbus RTU connection	LWPM 410	339410	0	
Outside temperature sensor with casing	FG 3115	336620	0	
Temperature sensor NTC-10 with metal sleeve	NTC-10M	363600	1	
<b>Accessories for passive cooling</b>				
Passive cooling controller	WPM Econ PK	360000	0	
Plate heat exchanger, copper-soldered	WTU 50	362370	0	
Plate heat exchanger for SI 50	WTE 50	358440	0	



Glen Dimplex Thermal Solutions  
 (Glen Dimplex Deutschland GmbH) T: + 49 9221 709-100  
 Am Goldenen Feld 18 F: + 49 9221 709-339  
 D-95326 Kulmbach dimplex@dimplex.de  
 www.dimplex.de

Glen Dimplex Austria GmbH  
 Hauptstraße 71  
 A-5302 Henndorf am Wallersee

T: + 43 6214 20330  
 F: + 43 6214 203304  
 info@dimplex.at  
 www.dimplex.at

# Data sheet WI 65TU

Description	Order ref.	Article number	Sample item	Item
Plate heat exchanger for SI 75	WTE 75	358450	0	
<b>Control accessories (cooling)</b>				
Room climate station for temperature and humidity measurement	RKS WPM	342220	0	
Dew point monitor	TPW WPM	350970	0	
<b>Solar thermal systems accessories</b>				
400l solar cylinder for heat pump	WWSP 432 SOL	361080	0	
500 l solar cylinder for heat pump	WWSP 540 SOL	361090	0	

\* Other specific accessories available / required

## Important information:

The combination of the components and the quantities indicated represent a non-binding sample system, which needs to be tested and individually adapted as required. Pump dimensioning must be reviewed according to the pressure loss of the system and the minimum heating water flow rate of the heat pump.



Glen Dimplex Thermal Solutions  
(Glen Dimplex Deutschland GmbH) T: + 49 9221 709-100  
Am Goldenen Feld 18 F: + 49 9221 709-339  
D-95326 Kulmbach dimplex@dimplex.de  
www.dimplex.de

Glen Dimplex Austria GmbH  
Hauptstraße 71  
A-5302 Henndorf am Wallersee

T: + 43 6214 20330  
F: + 43 6214 203304  
info@dimplex.at  
www.dimplex.at